

# 1-2-2 Wireshark 操作說明



Welcome to Wireshark

Capture

...using this filter:

區域連線 3

VMware Network Adapter VM

VMware Network Adapter VM

選擇介面卡

(1) 停止擷取

(2) 擷取封包紀錄

(3) 每一筆封包內容描述

(4) 封包內詳細資料

No.	Time	Source	Destination	Protocol	Length	Info
4	3.509716	fe80::fd0f:8d56:e73...	ff02::c	550P	208	M-SEARCH * HTTP/1.1
5	3.943199	Cisco_86:88:0f	Spanning-tree-(for-...	STP	60	Conf. Root = 32768/0/
6	4.141149	120.118.165.220	255.255.255.255	UDP	66	55424 → 5200 Len=24
7	5.027638	fe80::ec95:75d3:920...	ff02::1:3	LLMNR	84	Standard query 0x28b6
8	5.027761	120.118.165.117	224.0.0.252	LLMNR	64	Standard query 0x28b6
9	5.132521	fe80::ec95:75d3:920...	ff02::1:3	LLMNR	84	Standard query 0x28b6
10	5.132596	120.118.165.117	224.0.0.252	LLMNR	64	Standard query 0x28b6

Frame 6: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface 0

- Ethernet II, Src: HewlettP\_1c:98:15 (2c:27:d7:1c:98:15), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
- Internet Protocol Version 4, Src: 120.118.165.220, Dst: 255.255.255.255
- User Datagram Protocol, Src Port: 55424, Dst Port: 5200
- Data (24 bytes)

```
0000  ff ff ff ff ff ff 2c 27 d7 1c 98 15 08 00 45 00  .....E
0010  00 34 5e 51 00 00 80 11 be 15 78 76 a5 dc ff ff  4^Q.....xv...
0020  ff ff d8 80 14 50 00 20 12 de 44 4d 55 50 6e 50  ...P...DMUPnP
0030  5f 42 72 6f 61 64 63 61 73 74 3a 38 34 30 30 3a  _Broadca st:8400:
0040  31 30
```

